



Trinocular brightfield microscope, 1000x, N-PLAN objectives

Observation Method - Transmitted Light	Brightfield	Yes
	Darkfield	As optional
	Simple polarized light	As optional
Main Body	Type	Upright
	Construction material	Aluminum die-cast
	Trasportation handle	Yes
Head	Type	Trinocular (Siedentopf)
	Split ratio	50/50
	Inclination	30°
	360° rotating	Yes
	Interpupillary distance (mm)	48-75
	Diopter adjustment	On both tubes
	Fixing screw for eyepieces	Yes
	Tube inner diameter (mm)	23
Eyepieces	Field number (mm)	20
	Magnification	10x
	Pointer	As optional
	Micrometric scale	As optional
	Diameter of micrometer glass (mm)	21
	High eyepoint (for glass wearers)	Yes
	Rubber cup	Yes
Nosepiece	Positions	Quadruple
	Reversed	Yes
	Bi-directional	Yes
	Rotation on ball bearings	Yes
	Objective thread	RMS

Objectives	Optical system	160
	Anti-fungus treatment	Yes
	Parfocal distance (mm)	45
	Standard magnifications	40x-1000x
	Type	N-PLAN
		4x/0.10, W.D. 15.2 mm
		10x/0.25, W.D. 5.5 mm
		40x/0.65, W.D. 0.45 mm
Stage		100x/1.25 (Oil/Water), W.D. 0.13 mm
	Type	Double layer
	Dimensions (mm)	150x139
	Moving mechanism	Rackless
	Moving range (mm)	75x33
	Material	Anti-scratch painting
	Specimen holder	Yes
	Slide number	1
Condenser - Single Position	X-Y Vernier scale	Yes
	Vernier scale accuracy (mm)	0.1
	Type	Abbe
	Removable	Yes
	Numerical aperture (N.A.)	1.25
	Magnification scale for simplified positioning	Yes
	Diaphragm	Iris
	Centrable	Yes
Focusing System	Focusable	By rack and pinion
	Type	Coaxial coarse & fine
	Coarse total travel (mm)	18
	Fine total travel (per single rotation) (mm)	0,4
	Fine graduations	100
	Fine resolution (µm)	4
	Upper stop to prevent contact	Yes
	Adjustable tension	Yes
Transmitted Illumination	Kohler illumination	Fixed
	Type	X-LED
	X-LED type	X-LED3
	Light source power (W)	3.6
	Brightness control	Manual
	Lifetime (hours)	> 65,000
	Temperature (K)	6,300
	Max. required power (W)	6
Power Supply for Transmitted Illumination	Type	External
	Microscope connector	Jack, 2.1 mm
	Power plug type	Multi-plug (EU, UK, US)
	Input voltage	100/240 Vac, 50/60 Hz
	Output voltage	6 Vdc 2.5 A
Accessories Included	Dust cover	Yes
	Immersion oil (10ml)	Yes
	Tension adjustment tool	Yes
	User Manual	Digital version (downloadable)

Additional Information		Mirror for transmitted light (as optional). External rechargeable battery pack (as optional).
Product Dimensions	Height (mm)	440
	Width (mm)	235
	Depth (mm)	320
Product Weight		
	(kg)	6.5



WolfLabs

Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

www.wolflabs.co.uk

Tel : 01759 301142

Fax : 01759 301143

sales@wolflabs.co.uk

Please contact us if this literature doesn't answer all your questions.