EF 103 XSafe

Scotsman[®] Ice Systems

Self Contained Ice Machine 120 kg

| Item #: |
|-----------|
| Project: |
| Quantity: |



FEATURES

- Produces granular shape ice flakes, 80% hardness.
- Electronically controlled operation, with self-diagnostic functions with external alarm lights providing operational information for early alert and fast diagnosis of operating issues.
- External Components constructed from corrosion-resistant stainless steel crafted for optimal aesthetic appeal through superior fit and finish.
- Ergonomically convenient, slanted & disappearing storage bin door.
- Front access for easier naintenance.
- Front-in, front-out airflow allows for built-in installations.
- PWD Progressive Water Discharge: pumps excess residual water up to a distance of 15 meters.
- XSafe: natural sanitation system, integrated inside the ice maker and operating automatically 24/7 to keep equipment clean & safe.

Air cooled Water cooled

EF 103 Flake ice Residual water content 25% REFRIGERANT GAS

CONDENSING SYSTEM

R134a

VOLTAGE V/Hz/ph

230/50/1

INTERNAL BIN CAPACITY

30 kg

OPERATING REQUIREMENTS

| | Minimum | Maximum | | | |
|--------------------|----------------|----------------|--|--|--|
| Air temperature | 10 | 43 | | | |
| Water temperature | 5 | 38 | | | |
| Water pressure | 1 bar (14 psi) | 5 bar (70 psi) | | | |
| Electrical voltage | -10% | +10% | | | |
| | | | | | |

ORTANT NOTICE:

agion

RTIFICATION

lels and specifications are subject to ge without notice.
This spec sheet is meant for commercial purpose only.
For technical documentation please refer to our service manuals.

♦WRAS


SONCAP (LC


EF 103 XSafe


Scotsman[®] Ice Systems

Self Contained Ice Machine 120 kg


Item #:
Project:
Quantity:







AIR FLOW



UNIT OF MEASUREMENT: mm

- 1. 13/16" WATER OUTLET
- 2. 3/4" GAS WATER INLET
- 3. 3/4" GAS WATER OUTLET WATER COOLED UNIT ONLY
- 4. 3/4" GAS WATER INLET WATER COOLED UNIT ONLY
- 5. CORD SET

| l i | 105 |
|-----------------------------------|------|
| | 60 |
| | 55 4 |
| \$ 202 \$ 132 \$ 52 \$ 1 | • |

UNIT DATA

Size (W x D x H)
Net weight

592 x 622 x 1078 mm

68 kg

SHIPPING DATA

Carton (W x D x H)

670 x 690 x 1180 mm

Weight 76 kg

| - 1 | - | | | | | | | | | | | |
|-----|-----------------|----------|--|-----------|---------------------------|------|--------------------|--------------------------|-----|-------------------|----------------|----|
| | | | 24 h ice production kg °C Amb. / °C Water | | Energy consumption (*) | | Water usage (*) | Instant power Compressor | | (ircuit wires) . | Max. fuse size | |
| | | | 10°C/10°C | 21°C/10°C | 32°C/21°C | kWh/ | kWh/ | | | | | |
| | Version Voltage | kg | kg | kg | 100 kg | 24h | l/h | W | W | No. x Ømm² | A | |
| | EF 103 AS | 230/50/1 | 120 | 120 | 93 | 12.1 | 11.5 | 4.2 | 550 | 1200 | 3 x 1.5 | 10 |
| | EF 103 WS | 230/50/1 | 110 | 108 | 90 | 11.8 | 10.5 | 32.0 | 440 | 1200 | 3 x 1.5 | 10 |

(*) Data refer to 32°C Amb. / 21°C Water temperature conditions



Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

www.wolflabs.co.uk

Tel: 01759 301142

Fax: 01759 301143

sales@wolflabs.co.uk

Please contact us if this literature doesn't answer all your questions.