

CRYOSCIENCE

by Taylor-Wharton™

LS Series



LS Series

The Taylor-Wharton Laboratory Systems (LS) are uniquely designed for large vial capacity in convenient box-type storage racks. They provide maximum holding times. This means lower per vial operating costs and fewer refills. The new LS6000 with the AutoTend Controller with temperature read out provides automatic filling and alarm features.



Taylor-Wharton

LS Series

Models	LS750	LS3000	LS4800	LS6000	LS6000AT	
Static Holding Time days (1)	130	106	153	194	194	
Working Time days (2)	80	66	96	120	120	
Evaporation Rate (1) liters/days	0.27	0.76	0.85	0.84	0.84	
Liquid Nitrogen Capacity - liters	35	81	130	165	165	
Weight Empty	- lbs. - kg.	39 17.7	70 31.8	90 40.9	121 55.0	121 55.0
Weight Full (3)	- lbs. - kg.	101.3 46.0	214.2 97.4	312.4 146.1	410.0 186.4	410.0 186.4
Neck Diameter	- in. - mm.	4.7 119	8.5 216	8.5 216	8.5 216	8.5 216
Overall Height	- in. - mm.	26.8 681	28.8 731	35.1 892	39.0 991	39.0 991
Overall Diameter	- in. - mm.	18.8 478	26.9 683	26.9 683	26.9 683	26.9 683
Number of Racks	6	6	6	6	6	
Number of Shelves/Rack	5	5	8	10	10	
2 ml vial capacity (4)	750	3000	4800	6000	6000	
Box Size - Shape	Square	Square	Square	Square	Square	
Size in.	3.0 x 3.0	5.0 x 5.0	5.0 x 5.0	5.0 x 5.0	5.0 x 5.0	
Size mm.	76x76	127x127	127x127	127x127	127x127	
Vials per box (5)	25	100	100	100	100	
Roller Base	R033-8C00	R05K-8C00	R05K-8C00	R05K-8C00	R05K-8C00	
Cryo-Sentry Level Alarm	R036-8C30	RS30-8C40	R05K-8C26	RS60-8C40	N/A	
Auto Tend Controller Kit	N/A	N/A	N/A	RS60-8C86	N/A	

(1) Evaporation rate and static holding time are nominal. Actual rate may be affected by the nature of the contents, atmospheric conditions, container history, and manufacturing tolerances.

(2) Work time is an arbitrary, reference-only value to estimate container performance under the actual operating conditions.

(3) Without canisters or racks.

(4) 2.0 ml vial size: 12.5 mm O.D. internal thread

(5) 81 cell boxes available

Features

- (1) LS 6000 available with AutoTend Controller with temperature readout
- (2) LS 6000-AT, vapor phase, -190°C top of rack
- (3) New Rugged Construction – ribbed high strength aluminum body, magniformed necktube design, and more durable paint system
- (4) Convenient Storage Systems – rack index location ring and internal location spider, computer compatible box storage is ideal for simple inventory management
- (5) Superior vacuum performance with super insulation provides maximum holding times
- (6) Security – Accessory low-level alarm is available with remote monitor capability
- (7) Lockable lids
- (8) Mobility - Roller bases are available





WolfLabs

Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

www.wolflabs.co.uk

Tel : 01759 301142

Fax : 01759 301143

sales@wolflabs.co.uk

Please contact us if this literature doesn't answer all your questions.