



SE30-45P

Features and Benefits

- Static cooling
- Lock
- Castors
- Digital controller and temperature display
- 80mm insulation
- Defrost drain

Technical Specifications

Temperature Range	-5/-45°C
Refrigerant	R290
Type of Defrost	Manual
Exterior Finish	White
Interior Finish	White
Power Required	13 Amp
Max Ambient	30°C at 55% RH
Climate Class	4

Model	Description		Dimensions (mm)			Kg	Gross Int. Volume	No. of Baskets Supplied		Next Day
			H	W	D				Max	
SE10-45P	White Low Temp	Ext.	945	734	705	49	155ltr (5.5 cu.ft)	1	2	✓
		Int.	705	570	440					
SE20-45P	White Low Temp	Ext.	945	984	705	57	235ltr (8.3 cu.ft)	1	3	✓
		Int.	705	820	440					
SE30-45P	White Low Temp	Ext.	945	1284	705	71	330ltr (11.6 cu.ft)	1	5	✓
		Int.	705	1120	440					
SE40-45P	White Low Temp	Ext.	945	1504	705	78	400ltr (14.1 cu.ft)	1	6	✓
		Int.	705	1340	440					



EL51LT

Features and Benefits

- Static cooling
- Lock
- Feet
- Digital controller and temperature display
- Temperature alarm (visual only)
- 100mm insulation
- Defrost drain
- Baskets optional extra POA

Technical Specifications

Temperature Range	-10/-45°C
Refrigerant	R290
Type of Defrost	Manual
Exterior Finish	White
Interior Finish	Hammered Aluminium
Power Required	13 Amp
Max Ambient	30°C at 55% RH
Climate Class	4

Model	Description		Dimensions (mm)			Kg	Gross Int. Volume	Next Day
			H	W	D			
EL11LT	White Low Temp	Ext.	865	725	730	46	130ltr (4.6 cu.ft)	✓
		Int.	660	520	450			
EL21LT	White Low Temp	Ext.	865	1055	730	58	226ltr (8 cu.ft)	✓
		Int.	660	850	450			
EL31LT	White Low Temp	Ext.	865	1305	730	68	299ltr (10.6 cu.ft)	✓
		Int.	660	1100	450			
EL41LT	White Low Temp	Ext.	865	1505	730	82	358ltr (12.6 cu.ft)	✓
		Int.	660	1300	450			
EL51LT	White Low Temp	Ext.	865	1705	730	90	416ltr (14.7 cu.ft)	✓
		Int.	660	1500	450			